



# HS SERIES COAXIAL ARRAY SPEAKERS



***TOA presents yet another innovation in sound:  
The Coaxial Tweeter Array with  
large-diameter woofer.***

Sound that brings forth an emotional response.

# Cost-effective mid-size speaker system that high quality sound no matter what the applic



One of the most difficult speaker requirements to satisfy is a cost-effective mid-size speaker system that offers high quality sound no matter what the application. TOA HS Series speakers are equipped with narrow-directivity control (90° horizontal × 40° vertical). This useful feature allows tailoring the speaker's dispersion characteristics to better suit the acoustic environment in which it is installed.

The versatile HS-1200/1500 Series are compatible for use with 100V/70V lines for distributed applications. The HS Series speakers are exceptional in offering useful features at an attractive price.

## Large diameter woofer (12"/15") in a compact, lightweight enclosure

With its compact dimensions and light weight, the HS Series proves ideal for use in mid to small-size venues, including restaurants and pubs, conference rooms and lecture halls, schools and similar locations, as well as for temporary installations.

## Uniform high quality sound


is made possible by mounting the high frequency driver array in a coaxial configuration with the woofer.

- Extended bass frequencies for rich music reproduction
- Optimal sound delivery with well integrated low and high frequencies



## Optimal choice for acoustical problems caused by high ceilings

that tend to reduce the clarity of sound reproduction, such as in sports facilities, multi-purpose halls and houses of worship.




In locations with high ceilings, wide-directivity speakers cause the audio reaching the listeners to lose clarity due to overlapping of attenuated sounds.

offers  
ation.



### Coaxial Tweeter Array delivers accurate directivity control

HS Series speakers are equipped with narrow-directivity control (90° horizontal x 40° vertical). Well-balanced sound is delivered without treble attenuation to where the speaker is aimed, filling the acoustic space with clear sound.



### Versatile installation

Unobtrusive design makes an ideal choice for permanent installations.



Optional dedicated mounting brackets facilitates speaker installs on walls and ceilings.

### Accessory handle for easy transportability



### Secure floor setting



Accessory rubber feet for straight positioning.



Wedge-shape enclosure enables use as a floor monitor.

### Lineup:

12"/15" woofer, black and white finishes, low-impedance and high/low-impedance models are available.



### Twin input terminal sets

The speakon terminal is ideal for quick temporary installation and for testing purposes. The screw terminals are recommended for long-term installation.



# SPECIFICATIONS

Model No.	HS-120B	HS-120W	HS-1200BT	HS-1200WT
Enclosure			Sealed type	
Rated Power		Continuous pink noise: 100W, Continuous program: 300W		
Rated Impedance	8Ω		8Ω 100V line: 170Ω (60W), 330Ω (30W), 670Ω (15W) 70V line: 83Ω (60W), 170Ω (30W), 330Ω (15W), 670Ω (7.5W)	
Sensitivity		97dB (1W, 1m)		
Frequency Response	80 – 20,000Hz		70 – 20,000Hz	
Crossover Frequency		3kHz		
Directivity Angle		Horizontal: 90°, Vertical: 40°		
Speaker Component		Low frequency: 30cm (12") cone-type, High frequency: Balanced dome tweeter x 6		
Input Terminal		NEUTRIK NL4MP Speakon and M4 screw terminal, distance between barriers: 9mm		
Operating Temperature		-10°C to +50°C		
Finish	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white
Dimensions		361 (W) x 448 (H) x 320 (D)mm		
Weight	8.5 kg		10 kg	
Accessories	Handle x 1	Handle fitting bracket x 2, Handle mounting screw x 2, Rubber foot x 2, Rubber foot mounting screw x 2		
Options	Mounting bracket: HY-1200VB (for vertical speaker mounting) HY-1200HB (for horizontal speaker mounting) Ceiling mount bracket: HY-C0801 Wall mount bracket: HY-W0801 Speaker stand: ST-33B	HY-1200WW (for vertical speaker mounting) HY-1200HW (for horizontal speaker mounting) HY-C0801W HY-W0801W ST-33B	HY-1200VB (for vertical speaker mounting) HY-1200HB (for horizontal speaker mounting) HY-C0801 HY-W0801 ST-33B	HY-1200WW (for vertical speaker mounting) HY-1200HW (for horizontal speaker mounting) HY-C0801W HY-W0801W ST-33B

Model No.	HS-150B	HS-150W	HS-1500BT	HS-1500WT
Enclosure			Sealed type	
Rated Power		Continuous pink noise: 100W, Continuous program: 300W		
Rated Impedance	8Ω		8Ω 100V line: 170Ω (60W), 330Ω (30W), 670Ω (15W) 70V line: 83Ω (60W), 170Ω (30W), 330Ω (15W), 670Ω (7.5W)	
Sensitivity		98dB (1W, 1m)		
Frequency Response	70 – 20,000Hz		60 – 20,000Hz	
Crossover Frequency		3kHz		
Directivity Angle		Horizontal: 90°, Vertical: 40°		
Speaker Component		Low frequency: 38cm (15") cone-type, High frequency: Balanced dome tweeter x 6		
Input Terminal		NEUTRIK NL4MP Speakon and M4 screw terminal, distance between barriers: 9mm		
Operating Temperature		-10°C to +50°C		
Finish	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white
Dimensions		451 (W) x 560 (H) x 400 (D)mm		
Weight	12 kg		14 kg	
Accessories	Handle x 1	Handle fitting bracket x 2, Handle mounting screw x 2, Rubber foot x 2, Rubber foot mounting screw x 2		
Options	Mounting bracket: HY-1500VB (for vertical speaker mounting) HY-1500HB (for horizontal speaker mounting) Ceiling mount bracket: HY-C0801 Wall mount bracket: HY-W0801 Speaker stand: ST-33B	HY-1500WW (for vertical speaker mounting) HY-1500HW (for horizontal speaker mounting) HY-C0801W HY-W0801W ST-33B	HY-1500VB (for vertical speaker mounting) HY-1500HB (for horizontal speaker mounting) HY-C0801 HY-W0801 ST-33B	HY-1500WW (for vertical speaker mounting) HY-1500HW (for horizontal speaker mounting) HY-C0801W HY-W0801W ST-33B

## Optional Brackets

### For wall/ceiling mount



### For ceiling mount




### For wall mount



### Speaker Stand



\*To be used in conjunction with HY-1200/1500 Series brackets.



Human Society with  
Sound & Communication

TOA Corporation  
www.toa.jp

Specifications are subject to change without notice.  
Printed in Japan (0801) 833-61-653-70 u