

## DESCRIPTION

The F-2322CU2 ceiling-mounted speaker covers an extremely wide area and can be used for 25 and 70 V line applications. Well-balanced sound can be heard uniformly at any location.

## SPECIFICATIONS

Enclosure	Bass reflex type
Rated Input	30 W (High Impedance)
Power Handling Capacity	Continuous pink noise: 60 W (8 Ω) Continuous program: 120 W (8 Ω)
Impedance	70 V line: 170 Ω (30 W), 330 Ω (15 W), 1 kΩ (5 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W) 25 V line: 170 Ω (3.7 W), 330 Ω (1.9 W), 1 kΩ (0.6 W), 3.3 kΩ (0.2 W), 10 kΩ (0.06 W) 8 Ω
Sensitivity	90 dB (1 W, 1 m)
Frequency Response	70 Hz – 20 kHz at installation in 1/2 free sound field (Measured by installing the unit in the center of a ceiling.)
Speaker Component	12 cm (5") cone-type
UL Code	UL1480 (UEAY), UL2043, CAN/CSA C22.2 No.205 (UEAY7)
Mounting Hole	ø200 mm (7.87") (Maximum ceiling thickness: 37 mm (1.46"))
Input Terminal	Removable locking connector with screw-down terminals (2 input terminals and 2 bridge terminals)
Usable Cable	Solid copper wire: ø1.0 – ø1.6 mm (equivalent to AWG No. 18 – 14) Stranded copper wire: 0.75 – 2.5 mm <sup>2</sup> (equivalent to AWG No. 18 – 14)
Finish	Enclosure: Steel plate, plating Baffle: Fire-resistant ABS resin (resin material grade: UL-94 V-0), black Rim: Fire-resistant ABS resin (resin material grade: UL-94 V-0), white, paint Punched net: Steel plate, white, paint
Dimensions	ø230 × 209 (D) mm (ø9.06" × 8.23")
Weight	4.3 kg (9.48 lb) (including mounting accessories)
Accessory	Front grille ---1, Tile bridge ---1, Safety wire (approx. 60 cm (23.62")) ---1, Paper pattern ---1
Option	Back can: HY-BC1, Trim ring: HY-TR1

## APPEARANCE

