

MIXER AMPLIFIER

BG-2120(CU)

DESCRIPTION

The BG-2120 is a 120 W 5-input mixer amplifier for background music and general announcement. It is suited for use in bars, retail stores, and banquet rooms, and is equipped with the MOH OUT that permits 2-channel broadcast when used in conjunction with the optional booster amplifier BA-235 (35 W) or BA-260 (60 W).

■SPECIFICATIONS * 0 dB = 1 V

91 2011 10/1110110	* 0 dD = 1 V
Power Source	120 V AC, 60 Hz
Rated Output	120 W
Power Consumption	265 W (rated output), 120 W (based on cULus standards)
Frequency Response	50 Hz - 20 kHz
Total Harmonic Distortion	0.5 % or less, at 1 kHz, rated output
Input	Mic: -60 dB*, 600 Ω, electronically balanced, removable terminal block
	Line 1: −10 dB*/ TEL: −20 dB*
	Line 1/TEL selectable, 10 k Ω , electronically balanced, removable terminal block
	Line 2, 3: -10 dB* , $10 \text{ k}\Omega$, unbalanced, removable terminal block and RCA jacks
	Module
Output	Speaker: 4 Ω , 25 V (5.2 Ω), 70 V (42 Ω), balanced, removable terminal block
	MOH: 0 dB*, 600 Ω, balanced, removable terminal block
	Line: 0 dB*, 600 Ω, unbalanced, removable terminal block
Output Regulation	2 dB or less, no load to full load (1 kHz) On/Off switch for Mic, +24 V DC
Phantom Power	On/Off switch for Mic, +24 V DC
S/N Ratio	Mic: 60 dB or more, Line 1/TEL, Line 2, 3, Module: 75 dB or more
	(Band Pass: 20 Hz — 20 kHz, Tone Controls: Centered)
Muting	Manual mute/Automatic mute
Tone Control	Bass: ±10 dB at 100 Hz, Treble: ±10 dB at 10 kHz
Control	Mic gain control, Line 1/TEL gain control, Line 2 gain control, Line 3 gain control,
	Module gain control, Bass tone control, Treble tone control, MOH out gain control,
	Mute control (Manual mute), Remote volume control, Mute sense control,
	Line 1/TEL selector switch, Phantom power switch (Mic),
	Auto mute switch (Mic, Line 1/TEL, Module),
	Mute receive switch (Mic, Line 1/TEL, Line 2, 3, Module),
	MOH assign switch (Mic, Line 1/TEL, Line 2, 3, Module), Power ON/OFF switch
Indicator	Power LED, Signal level LED, Peak LED
Operating temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	35 % to 80 %RH (no condensation)
Finish	Panel: ABS resin, black
	Case: Steel plate, black, paint
Dimensions	264 (W) × 94.3 (H) × 267.3 (D) mm (10.39" × 3.71" × 10.52")
Weight	6 kg (13.23 lb)
Accessory	Volume control cover: YA-9205, Removable terminal plug (2 pins)4,
	Removable terminal plug (3 pins) -2, Removable terminal plug (4 pins) -1,
	Removable terminal plug (5 pins) ···1, AC fuse ···1
Option	Rack mounting bracket: MB—1000

APPEARANCE

