

SUBWOOFER SYSTEM

FB-100

■DFSCRIPTION

The TOA FB—100 is a high—power subwoofer system employing an enclosure of Acoustic Super Woofer construction.

■SPECIFICATIONS

Enclosure	Acoustic Super Woofer
Power Handling Capacity	450 W (Continuous program, 40 - 200 Hz)
	150 W (Continuous pink noise, 40 - 200 Hz)
Rated Impedance	8 Ω
Sound Pressure Level	88 dB (1 W, 1 m) installation in free sound field
	(Measured in anechoic chamber.)
	94 dB (1 W, 1 m) installation in 1/2 free sound field
	(Measured by installing the unit in the center of
	a ceiling or wall.)
Frequency Response	35 — 160 Hz (—10 dB) installation in 1/2 free sound field
	(Measured by installing the unit in the center of
	a ceiling or wall.)
Speaker Component	25 cm cone speaker
Input Terminal	Detachable screw terminal, (+)/(-) 2 each (for bridging connection)
Usable Cable	Solid cable, stranded cable: 0.2 — 2.5 mm² (AWG No.24 — 14)
Finish	MDF, black, paint
Dimensions	354 (W) × 582 (H) × 340 (D) mm
Weight	16 kg
Option	Matching transformer: MT-S0601 (rated 60 W)

■APPEARANCE

