

DIRECT SELECT UNIT

N-8000DI(CE/CE-GB)

The N-8000DI is a Direct select unit designed for use with TOA's packet intercom system (IP network-compatible intercom system) that employs the packet audio technology. It is equipped with each 32 contact inputs and outputs, and the indicators on the front panel indicate the output statuses.

Connecting the unit to the LAN permits the calling station display, external equipment control, and direct selection function to be realized.

It can be mounted in an EIA equipment rack (1U size) with the use of an accessory rack mounting bracket or installed on a wall using an optional wall mounting bracket.

■ SPECIFICATIONS

220 - 240 V AC, 50/60 Hz
16 W (max.)
32 inputs, no-voltage make contact input, open voltage: 24 V DC,
short—circuit current: 5 mA or less, removable terminal block (20 pins)
(1 common terminal for 4 inputs)
32 outputs, relay contact output, contact capacity: 24 V DC/2 - 500 mA,
removable terminal block (32 pins)
Network I/F: 10BASE-T/100BASE-TX (Automatic-Negotiation)
Network protocol: TCP/IP, UDP, HTTP, RTP, ARP, ICMP, IGMP
Connector: RJ45 connector
Network LNK/ACT indication, Status lamp, Power—on indication lamp,
Channel indication lamps (32 channels)
Firmware update function, System data hold function, Time of day hold facility,
Reset switch (front panel)
Rack, Desk, Surface mount
0 °C to +40 °C (32 °F to 104 °F)
90 %RH or less (no condensation)
Pre-coated steel plate, black, 30 % gloss
420 (W) × 44.3 (H) × 267 (D) mm (16.54" × 1.74" × 10.51")
2.8 kg (6.17 lb)
Power cord (2 m (6.56 ft)) ···1, CD (for PC setting, maintenance use) ···1,
Removable terminal plug (10 pins)4, Removable terminal plug (16 pins)4,
Plastic foot4, Screw for fitting plastic foot4, Rack mounting bracket2,
Screw for mounting bracket8, Screw for rack mounting4
Wall mounting bracket: YC-850

■ APPEARANCE

