■DESCRIPTION

Designed for exclusive use with the 9000M2 Series amplifier or M-864D, the ZM-9014 is a wall mounted remote control panel having 4 buttons and 1 volume control knob. It is used in conjunction with the RC-001T Remote control module or M-864D. It can be mounted in an American standard 2-gang electrical box in the wall.

■ SPECIFICATIONS

Power Source	24 V DC (supplied from RC-001T or M-864D)
Current Consumption	50 mA or less
Terminal	Removable terminal block (10 pins)
Connection Cable	Shielded CPEV cable (paired data line and paired power line) or
	Category 5 twisted pair cable for LAN (CATS—STP)
Operating Section	4 function buttons, 1 volume control
Indicator	4 function indicators (green LEDs), Level indicators (green LEDs)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	35 % to 80 %RH (no condensation)
Finish	Surface—treated steel plate, white, paint
Dimensions	120 (W) × 127 (H) × 58.5 (D) mm (4.72" × 5" × 2.3")
Weight	374 g (0.82 lb)
Accessory	Box mounting screw (No.6-32UNC \times 30)4,
	Box mounting screw (M4 × 30) ···4, Panel mounting screw ···4,
	Removable terminal plug (10 pins) ···1

Note: Since no electrical box is supplied with the unit, prepare it separately.

