TOA FLUSH CEILING MOUNTING BRACKET C-BC704U

■DESCRIPTION

The C-BC704U bracket is designed to be exclusively used for flush ceiling mounting of the optional C-CC704 combination camera. Use this bracket when mounting the camera to the ceiling surface where the fixing screws cannot be securely installed, such as on the plaster panel of the dual-construction ceiling. Also, use this bracket to minimize the exposure of the camera.
It is designed for indoor use only.

■SPECIFICATIONS

Board Thickness for Mounting	30 mm (1.18") or less
Applications	Indoors
Finish	Base: Surface-treated steel plate Decorative frame: ABS resin, light gray, paint
Mounting Hole	⌀188 to 192 mm (⌀7.4" to 7.56")
Dimensions	⌀207 × 144 (H) mm (⌀8.15" × 5.67")
Weight	450 g (0.99 lb)
Accessory	Safety wire ⋯1, Camera mounting bracket ⋯3, Camera fixing screw ⋯3, Decorative frame fixing screw⋯1

■APPEARANCE

11 [0.43"]

Safety wire (accessory) mounting hole
(for flush ceiling mounting bracket)

Safety wire mounting hole (for camera)

Top View

Anchor bolt fixing section

155 [6.1"]

Front View

144 [5.67"]

⌀207 [⌀8.15"]

Side View

Bottom View

Safety wire (accessory)
(Connect this wire to an object other than the bracket.)

Anchor bolt

30 mm [1.18"] or less

Ceiling board

Ceiling mounting

Note: The mounting hole in the ceiling is ⌀188 to 192 mm (⌀7.4" to 7.56") in diameter.

Decorative frame fixing screw hole

C-CC704(option)

UNIT: mm   SCALE: 1/4