

DESCRIPTION

The C-CH210FH camera housing is designed to house a television camera, fixed focal length lens, zoom lens and other components to protect them from the direct sunlight, wind and rain when they are installed outdoors. The C-CH210FH is equipped with a heater, a fan, a defroster, and a wiper.

SPECIFICATIONS

Power Source	24 V AC, 50/60 Hz
Current Consumption	Fan: 4.6 W Heater: 19 W Defroster: 5 W Wiper: 2.3 W
Fan/heater Operating Temperature	Fan: Turns on at approx. 26 °C or more Heater: Turns on at approx. 10 °C or less Defroster: Turns on at approx. 30 °C or less, and turns off at approx. 50 °C or more
Operating Temperature	-20 °C to +45 °C (If the wiper driving section is frozen, the wiper does not correctly work.)
Operating Humidity	30 % to 98 %RH
Application	Indoors and outdoors (except seaside and industrial districts where the unit is subject to corrosion, and heights that expose the unit to strong wind pressure)
Waterproof/Dustproof Capability	IP54
Finish	Unit: Aluminum extrusion, off-white, paint Panel: Die-cast aluminum, off-white, paint
Dimensions	195 (W) × 207 (H) × 500 (D) mm
Weight	6 kg
Accessory	Camera mounting bolt ---2, Housing fixing bolt ---4, Washer ---1set, Coaxial cable for internal wiring ---1, Zoom lens cable for internal wiring ---1, Camera power supply cable (for 24 V) for internal wiring ---1
Applicable Camera	C-CC364(*1), C-CV14-CS, N-CC2360(*2)
Option	Housing fixing stand: C-BC200H Wall mounting bracket: C-BC200K Pan/tilt head: C-PH200

(*1) Unusable in combination with CT-0312GB, CT-R2VFG.

(*2) Unusable in combination with CT-0312GB, CT-10ZMGA, CT-21ZMG, CT-6ZMG, or CT-R2VFG.

APPEARANCE
