

## DESCRIPTION

The F-240WM is a compact, 2-way bass reflex speaker system that provides wide range reproduction. High impedance applications are possible with an internally mounted line matching transformer.

## SPECIFICATIONS

Enclosure	Bass-reflex type
Rated Input	30 W
Rated Impedance	100 V line: 330 $\Omega$ (30 W), 500 $\Omega$ (20 W), 1 k $\Omega$ (10 W), 2 k $\Omega$ (5 W) 70 V line: 170 $\Omega$ (30 W), 330 $\Omega$ (15 W), 500 $\Omega$ (10 W), 1 k $\Omega$ (5 W), 2k $\Omega$ (2.5 W) (Selection by rotary switch)
Sound Pressure Level	92 dB (1 W, 1 m)
Frequency Response	65 – 20,000 Hz
Crossover Frequency	4 kHz (passive network)
Speaker Component	Low frequency: 16 cm cone-type High frequency: 3 cm dome-type (titanium diaphragm)
Input Connector	Push terminal
Finish	Enclosure: Polypropylene, white, semi-gloss Punched net: Steel plate, white, paint
Dimensions	355 (W) $\times$ 210 (H) $\times$ 226 (D) mm
Weight	5.5 kg
Option	Speaker bracket: WCB-31W (for wall), CMB-31W (for ceiling)

## APPEARANCE

