

IP PAGING GATEWAY

IP-A1PG

DESCRIPTION

The IP—A1PG is a PoE—powered Gateway Unit that integrates multiple IP Audio devices by converting the audio from Video Management Systems using ONVIF or voice from SIP Phone systems into multicast audio streaming. It can also transmit built—in sound source or input audio as multicast audio streaming. Moreover, the event broadcasting triggered by control input, scheduler or remote API (HTTP) as well as the command set that sends multiple HTTP commands simultaneously are also available.

■ SPECIFICATIONS

D 0	
Power Source	PoE(IEEE802.3af Class 3)
Power Consumption	2.5 W
Audio Transmition Method	Multicast Audio Streaming
Audio Codec	Opus, PCMU(G.711u), PCMA(G.711a), G.722
Audio Delay Time	Min. 100 ms (*1)
Network I/F	100BASE-TX, Auto MDI/MDI-X, RJ45 connector
Network Protocol	TCP/IP, UDP, HTTP, RTP, RTSP, RTCP, ARP, ICMP, IGMPv3, NTP, SIP(RFC3261)
Audio Input	1 channel, electronically—balanced, 10 kΩ
	LINE/MIC selectable (Rated input: LINE: 0 dB (*2), MIC: -60 dB (*2))
	PAD function (-20 dB (*2)), Phantom power ON/OFF (12 V DC), volume adjustable
	removable terminal block (6 pins)
Monitor Output	1 channel, unbalanced, 600 Ω or less
i i	Rated output: 0 dB (*2), RCA pin jack
Control Input	4 channels, no-voltage make contact inputs, open voltage: 5 V DC,
i '	short-circuit current: 2 mA or less, removable terminal block (6 pins)
Mute Control Input	1 channel, 24 V DC cut signal, control current: 5 mA or less,
'	removable terminal block (2 pins)
Control Output	1 channel, open collector output, withstand voltage: 30 V DC,
	control current: 150 mA or less, removable terminal block (6 pins)
Indicator	control current: 150 mA or less, removable terminal block (6 pins) STATUS (green/blue/yellow/red), LINE/MIC IN (green/red), OUTPUT (green), LINK/ACT (green)
Functions	,
Broadcasting	Audio transmission
J. caacacting	Transmit internal messages by multicast audio streaming
	Transmit audio from audio input connected devices by multicast audio streaming
	Audio conversion
	Convert SIP voice to multicast audio stream and transmit
	Convert audio from Video Management Systems using ONVIF to multicast audio
	stream and transmit
Scheduler	Scheduled broadcasting and control by WEB-UI (Max. schedule settings: 2000)
Schledarer	Configurable actions: Internal message broadcast, audio input broadcast,
	control output, command set transmision
Event	Execute event triggered by control input
Event	Configurable actions: Internal message broadcast, audio input broadcast,
	command set transmission, broadcast disable, system mute
Sound Source Files	Max. 20 files (File storage capacity: 80 MB total)
Journa Jource Files	Supported fie format:
	WAV file: 8/16/44.1/48 kHz sampling frequency, 8/16 bit, monaural/stereo
	MP3 file: 32/44.1/48 kHz sampling frequency, 64 - 320 kbps, CBR/VBR, monaural/stereo
	Repeat playback: Playcount (1 - 10 times) or Duration (5 - 3600 sec)
Command Set	Interval time: 0 - 99 sec, Delay time: 0 - 99 sec 20 commands can be registered in each of 10 command sets
Communa Set	20 communds can be registered in each of 10 commund sets
Clock Acquiracy	117 geografia per month
Clock Accuracy	±13 seconds per month
Time Adjustment	Manual time setting, Time adjustment by NTP server
Power Outage Protection	24 hours (RTC time retention, at 40 °C (104 °F))
Period	Firstlish / Januara
Language	English/Japanese
Operating Temperature	-30 °C to +55 °C (-22 °F to 131 °F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Front case: Surface—treated steel plate, black, paint
D: .	Rear chassis: Surface—treated steel plate
Dimensions	126 (W) × 33 (H) × 80 (D) mm (4.96" × 1.3" × 3.15") (excluding projection)
Weight	390 g (0.86 lb)
Accessory	Removable terminal plug (6 pins, preinstalled on the unit)2,
	Removable terminal plug (2 pins, preinstalled on the unit) …1, Rubber feet …4,
	Mounting screw (M3 × 6) ···4
(+1) When using Monitor	output googge an gudio delay timo

^(*1) When using Monitor output, assume an audio delay time. (*2) 0 dB = 1 $\mbox{\rm V}$

^{*} ONVIF is a registered trademark of ONVIF Inc.

^{**} These specifications apply to the firmware version 3.1.0 or later. For the latest specifications and firmware, please refer to the TOA DATA Library (https://www.toa-products.com/international/).



IP PAGING GATEWAY

IP-A1PG


ISPECIFICATIONS

Personal Computer Requirements


Display	1920 × 1080 resolution or greater
OS	Windows 10 Pro (64-bit edition)
	Windows 10 Home (64-bit edition)
	Windows 11 Pro
	Windows 11 Home
Required Web Browser	Google Chrome
·	Microsoft Edge

- ** Windows and Microsoft Edge are registered trademarks of Microsoft Corporation in the United States and other countries.
- * Google Chrome is the trademark of Google LLC in the United States and other countries.
- * Other company names and products are also trademarks of individual companies.


APPEARANCE




Rear View



Front View





(with accessories)

Top View

UNIT: mm SCALE: 1/2

Note: Numerical values in parentheses are for reference only.